

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM

ACCESS CONTROL

DS-K1802M/E
Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard

DS-K1802MK/EK
Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard
- With keypad

DS-K1F810-F
Fingerprint Card Issuer



- 500 dpi high-definition
- Support the function of PnP(plug and play)
- Optical fingerprint sensor designed with scratch-resistant materia
- USB 2.0 communication standard for data transmission

DS-K1F180-D8E
Card Issuer



- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card and EM card)
- Supports on-line upgrade

DS-K1107E/EK
DS-K1107E/EK



- Support EM card,
- With keypad (DS-K1107EK)
- Supports RS485 and Wiegand (W26/W34) protocol,
- IP65 Standard

DS-K1107M/MK
Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1107MK)
- Supports RS485 and Wiegand (W26/W34) protocol,
- IP65 Standard

DS-K1200EF/MF
Fingerprint Card Reader



- Support fingerprint Mifare 1/EMcard
- Supports RS485 protocol,
- IP65 Standard
- 9500 Fingerprints Capacity

DS-K2M060
Secure Module



- Provide secure door control as well as I/O expansion via encrypted communication when combined with other Hikvision terminal.
- Support RS485 protocol

DS-K1T803F
Fingerprint Access Control Terminal



- Support Access Control and Time Attendance Function
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.4-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation

DS-K1T803MF/EF
Fingerprint Access Control Terminal



- Support Access Control and Time Attendance Function
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.4-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation
- Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc

DS-K1A801F
Fingerprint Time Attendance Terminal



- Support Time Attendance Function, Forming Reports Automatically
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.8-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation(Adding Person & Card & Fingerprints Locally)

DS-K1A801MF/EF
Fingerprint Time Attendance Terminal



- Support Time Attendance Function, Forming Reports Automatically
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.8-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation(Adding Person & Card & Fingerprints Locally)
- Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc

DS-K2801
Single-door Access Controller



- Accessible Card Reader: 2 Wiegand readers
- Input interface: 1 Door Magnetic, 1 Door Switch, 1 Case Input
- Output interface: 1 Door Switch Relay, 1 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

DS-K2802
Double-door Access Controller



- Accessible Card Reader: 4 Wiegand readers
- Input interface: 2 Door Magnetic, 2 Door Switch, 2 Case Input
- Output interface: 2 Door Switch Relay, 2 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

DS-K2804
Four-door Access Controller



- Accessible Card Reader: 4 Wiegand readers
- Input interface: 4 Door Magnetic, 4 Door Switch, 4 Case Input
- Output interface: 4 Door Switch Relay, 4 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

DS-K1T801M/E
Time & Attendance and Access Control Terminal



- 12 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- Max. 3000 card number settings
- Supports door-open button

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM

DS-K1T802M/E

Time & Attendance and Access Control Terminal



- 128x64 Dot Matrix STN Screen
- 12 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- Supports door-open button
- Storage with 3,000 cards information and 10,000 access control events

DS-K1801MK/EK

Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard
- With keypad

DS-K1801M/E

Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard

DS-K1F100-D8E

Card Enrollment Station



- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card, CPU, PSAM, and EM card)
- Supports on-line upgrade

DS-K2601

Single door Access Controller



- Accessible Card Reader: 2 Wiegand readers & 2 RS485 readers
- Input interface: 4 Alarm Input, 1 Door Magnetic, 1 Door Switch, 2 Case Input, 1 Tamper-proof
- Output interface: 1 Door Switch Relay, 1 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

DS-K2602

Double-door Access Controller



- Accessible Card Reader: 4 Wiegand readers & 4 RS485 readers
- Input interface: 4 Alarm Input, 2 Door Magnetic, 2 Door Switch, 4 Case Input, 1 Tamper-proof
- Output interface: 2 Door Switch Relay, 2 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

DS-K2604

Four door Access Controller



- Accessible Card Reader: 4 Wiegand readers & 8 RS485 readers
- Input interface: 4 Alarm Input, 4 Door Magnetic, 4 Door Switch, 8 Case Input, 1 Tamper-proof
- Output interface: 4 Door Switch Relay, 4 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

DS-K1T105M/E(-C)

Standalone Access Control Terminal



- 2.8 inch LCD -TFT Screen
- 16 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- 2 Megapixels camera(Optional)
- Supports WiFi function
- Storage with 100,000 cards information and 300,000 access control events

DS-K1T200MF/EF(-C)

Standalone Access Control Terminal



- 2.8 inch LCD -TFT Screen
- 16 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- 2 Megapixels camera(Optional)
- Supports WiFi function
- Storage with 100,000 cards information and 300,000 access control events

DS-K1101M(K)

Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1101MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 120 Gang Box Only

DS-K1102M(K)

Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1102MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box

DS-K1102E(K)

Card Reader



- Support EM card,
- With keypad (DS-K1102EK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box

DS-K1104M(K)

Vandal Proof Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1104MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box
- Vandal Proof

DS-K1F800-F

Fingerprint Card Issuer



- 500 dpi high-definition
- Support the function of PnP(plug and play)
- Optical fingerprint sensor designed with scratch-resistant material
- USB 2.0 communication standard for data transmission

IC S50

Mifare 1 Non-contacting IC Card



- Working frequency: 13.56 MHz
- Anti-conflict
- Long time data storage for 10 years
- Triple accreditation(ISO/IEC DIS9798-2)

DS-K4T100

Electric Bolt



- Support Thrust of 800Kg;
- Polished and Brushed Stainless Steel
- Working Current: 900mA(Startup Current) , 100mA(Standby)
- DC12V

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM

DS-K4H250S
Magnetic Lock



- Single -door Control
- Supports static linear thrust of 300kg
- Working Current: DC12V(500 mA) / 24VAC(250 mA)

DS-K4H250D
Magnetic Lock



- Double-door Control
- Supports static linear thrust of 2x300kg
- Working Current: 12V/500mA × 2 24V/250mA × 2

DS-K4T100-U1/2
Accessories of Electric Bolt



- Aluminum alloy material
- Suitable for fully frameless glass door
- The door opens both sides at the angle of 180°

DS-K4H250-LZ/U
Accessories of Magnetic Lock



- Adopts aldural material with the surface sandblast
- The shell is hard anodizing electroplating operated

DS-K7P01/02
Exit Button



- Aluminum alloy panel with sandblast, metal button
- Already passed 500 thousand times aging test
- NO/NC/COM Contact
- 3A@36VDC Max

DS-K7P03/04
Exit Button



- Infrared Sensor
- Panel: aluminum panel
- Already passed 1 million times aging test
- NO/NC/COM Contact
- 1A@30VDC, 0.5A@125VAC

DS-K7P05/06
Exit Button



- Infrared Sensor
- Brushed stainless steel panel, metal button
- Already passed 500 thousand times aging test
- NO/NC/COM Contact
- 3A@36VDC Max

DS-K7PEB
Emergency Break Glass



- Suitable for exit door and emergency door
- Fireproof material, sandblast finished
- NO/NC/COM Contact
- 3A@36VDC Max

INTRUSION ALARM

DS-19A08-F/Kx(6)
8 Zone Network Security Control Panel



- PTSN, 10/100Mbps Ethernet
- LED screen (DS-19A08-F/K1)
- LCD screen (DS-19A08-F/K2)
- 1 relay output
- 14.3 VDC

DS-19S08-04F/Kx(6x)
8 Zone Video Security Control Panel



- 4-ch 960H analog video input
- PTZ control
- LED screen (DS-19S08-04F/K1)
- LCD screen (DS-19S08-04F/K2)
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19S08N-04F/Kx(6x)
8 Zone Video Security Control Panel



- Support 4-ch IPC video input, Max 25 Mbps
- PTZ Control
- LED screen (DS-19S08N-04F/K1)
- LCD screen (DS-19S08N-04F/K2)
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19A00-BN
8/16 Zone Video Control Panel



- PTSN, 10/100Mbps Ethernet
- 4 relay output, 220 VAC

DS-19S00-04S(Gx)
8/16 Zone Video Security Control Panel



- 4-ch 960H analog video input
- PTZ Control
- 1-ch VGA output, 1-ch HDMI output
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19S00N-04S(Gx)
8/16 Zone Video Security Control Panel



- Support 4-ch IPC video input, support dual-stream
- PTZ Control
- 1-ch VGA output, 1-ch HDMI output
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-1T21FZ
Dual-technology Detector



- CLOAK WISETM arithmetic
- Tempering-proof bracket
- Sealing optical system
- The IR and microwave working distance is 15m X 15m

DS-1T070R
Shock Detector



- The zinc-aluminum alloy enclosure is antistatic and anti-interference
- The sensitivity is adjustable
- Ceramics sensor, with high temperature & humidity adaptation and corrosion resistance
- Function of low battery and tampering alarm

ACCESS CONTROL INTRUSION ALARM & VIDEO INTERCOM

VIDEO INTERCOM

DS-19K00-B(X)
LED Alarm Keypad



- Supports remote control via wireless network(the keypad with model of RF)
- Prompts alarm with the indicators and audio alert
- Operates on the security control panel through programming
- LED display, RS485 interface

DS-19K00-BL
LCD Alarm Keypad



- Supports remote control via wireless network(the keypad with model of RF)
- Prompts alarm with the indicators and audio alert
- Operates on the security control panel through programming
- LCD display, RS485 interface

DS-19M00-R0
Trigger Extension Module



- RS-485 trigger extension module
- 8 DIP address
- 4/8-ch trigger Output

DS-KB8112-IM
vandal-proof villa door station



- HD video surveillance with WDR wide angle and high performance CMOS, up to 720P @ 30 fps
- Support Web remote access and OSD display
- Support ISAPI and ONVIF
- IK 9 and IP 66
- Access control function
- Motion detection

DS-KAD606-N
Distributor



- Built-in 24 VDC voltage-stabilized switching mode power supply
- 8 interfaces of RJ-45, including six adaptive 10/100 Mbps LAN interfaces

DS-KB2411-IM
Door Station



- Pinhole Camera with 720*576 @ 25 fps
- Video Intercom Communication
- Support Two Door Stations Cascading in Intercom System
- Unlocking Controlling
- Self-adaptive IR Supplement

DS-KH2200
Indoor Station



- 7-inch LCD Screen
- Video Intercom Communication
- Support Three Indoor Stations Cascading in Intercom System
- Remote Unlocking
- Monitoring Door Station and External Analog Camera

DS-KD8102-V
Plastic Door Station



- 3.5-inch Colorful TFT LCD, display resolution: 480 * 320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M/1000M Self-adaptive Ethernet
- 8-ch alarm input, 4-ch alarm output
- IR detection
- Visible Light Supplement

DS-KD8002-VM
Metal Door Station



- 3.5-inch Colorful TFT LCD, display resolution: 480 * 320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M/1000M Self-adaptive Ethernet
- 8-ch alarm input, 4-ch alarm output
- Visible Light Supplement

DS-KV81/2/402-IM
Metal Villa Door Station



- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M Self-adaptive Ethernet
- 4-ch alarm input, 1-ch alarm output
- IP 65 and IR Supplement
- 1/2/4-ch Indoor station access

DS-KV8102-IP/VP
Plastic Villa Door Station



- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M Self-adaptive Ethernet
- 4-ch alarm input, 1-ch alarm output
- IP 65
- 1-ch Indoor station access
- Visible Light Supplement(-VP), IR Supplement(-IP)

DS-KH8300/DS-KH8301-WT
Indoor Station



- 7-inch Colorful TFT LCD, display resolution: 1024 * 600
- 10M/100M Self-adaptive Ethernet
- Camera resolution: 640 * 480, Mechanical Switch, Wi-Fi 802.11b/g/n, support SD card (DS-KH8301-WT)
- 8-ch alarm input
- Power Over Network Cable/ 12 VDC

DS-KH6310(-W)
Indoor Station



- 7-inch Colorful TFT LCD, display resolution: 800 * 480
- 10M/100M Self-adaptive Ethernet
- Wi-Fi 802.11b/g/n (-W)
- 8-ch alarm input
- Power Over Network Cable/ 12 VDC

DS-KAD606/612
Distributor



- Built-in voltage-stabilized power
- Suitable for indoor monitor station and villa door station
- 8 x 100Mbps ports(6-ch network cable powering and 2-chcascading LAN interfaces) (DS-KAD606)
- 16 x 100Mbps ports(12-ch network cable powering and 4-chcascading LAN interfaces) (DS-KAD612)

DS-KM8301
Master Station



- 7-Inch Colorful TFT LCD, display resolution: 1024 * 600
- Capacitive Touch Screen, Touch Key, Physical Key
- 10M/100M/1000M Self-Adaptive Ethernet
- SIP services
- 2 RS-485, 4 On-Off Input, 2 On-Off Output, 2 Relay Output,

DS-KAW50-1
Power Supply



- Power supply for Door station and Villa Door Station
- Output: 12 VDC, 4.2A

DS-KAW50-1N

Power Supply



- Input Voltage:100-240VAC
- Output Voltage:12VDC
- Output Current: 4.17A
- Output Power: 50W
- Short circuit protection, over load protection, and over power voltage protection

DS-KAB01

Protective Shield



- Stainless steel material
- Convenient design available for villa door station wall mounting
- Avoid of being directly exposed to the sun
- Rain shield and mounted box are separated.

DS-KAB02

Protective Shield



- Stainless steel material
- Convenient design available for villa door station wall mounting
- Avoid of being directly exposed to the sun

COMPRESSION CARDS

DS-4304HFHI-E

HD1080P Compression Card



- 4-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@1920×1080P resolution real-time recording
- HDMI output at up to 1920×1080P resolution
- PCI-Ex1 2.0 standard
- OSD, LOGO and mask area settings

DS-4308/16HWI-E

Full 960H Compression Card



- 8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@WD1(PAL:960×576,NTSC:960×480) resolution
- real-time recording
- PCI-Ex1 2.0 standard
- OSD,LOGO and MASK overlay

DS-4304/08/16HFVI-E

Full 4CIF Compression Card



- 4/8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@4CIF resolution real-time recording
- PCI-Ex1 2.0 standard
- OSD,LOGO and MASK overlay